

FORM PTO-1390

U.S. DEPARTMENT OF COMMERCE PATENT AND TRADEMARK OFFICE

ATTORNEY'S DOCKET NUMBER

**TRANSMITTAL LETTER TO THE UNITED STATES
DESIGNATED/ELECTED OFFICE (DO/EO/US)
CONCERNING A FILING UNDER 35 U.S.C. 371**

50212-207

U.S. APPLIC. NO. (if known, see 37 CFR 1.5)

09/830939

INTERNATIONAL APPLICATION NO

INTERNATIONAL FILING DATE

PRIORITY DATE CLAIMED

PCT/JP99/06039

October 29, 1999

November 3, 1998

TITLE OF INVENTION

OPTICAL FIBER DRAWING METHOD AND OPTICAL FIBER DRAWING FURNACE

APPLICANT(S) FOR DO/EO/US

Toshiki TARU, Ichiro TSUCHIYA, Katsuyuki TSUNEISHI, Katsuya NAGAYAMA, and Kazuya KUWAHARA

Applicant herewith submits to the United States Designated/Elected Office (DO/EO/US) the following items and other information:

1. ☒ This is a **FIRST** submission of items concerning a filing under 35 U.S.C. 371.
2. ☐ This is a **SECOND** or **SUBSEQUENT** submission of items concerning a filing under 35 U.S.C. 371.
3. ☒ This express request to begin national examination procedures (35 U.S.C. 371(f)) at any time rather than delay examination until the expiration of the applicable time limit set in 35 U.S.C. 371(b) and PCT Articles 22 and 39(1).
4. ☒ A proper Demand for International Preliminary Examination was made by the 19th month from the earliest claimed priority date.
5. ☒ A copy of the International Application as filed (35 U.S.C. 371(c)(2))
 - a. ☐ is transmitted herewith (required only if not transmitted by the International Bureau).
 - b. ☒ has been transmitted by the International Bureau
 - c. ☐ is not required, as the application was filed in the United States Receiving Office (RO/US)
6. ☒ A translation of the International Application into English (35 U.S.C. 371(c)(2)).
7. ☐ Amendments to the claims of the International Application under PCT Article 19 (35 U.S.C. 371(c)(3))
 - a. ☐ are transmitted herewith (required only if not transmitted by the International Bureau).
 - b. ☐ have been transmitted by the International Bureau
 - c. ☐ have not been made; however, the time limit for making such amendment has NOT expired
 - d. ☐ have not been made and will not be made
8. ☐ A translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371(c)(3)).
9. ☒ An oath or declaration of the inventor(s) (35 U.S.C. 371(c)(4)).
10. ☐ A translation of the annexes to the International Preliminary Examination Report under PCT Article 36 (35 U.S.C. 371(c)(5)).

Items 11. to 16. below concern other document(s) or information included:

11. ☒ An Information Disclosure Statement under 37 CFR 1.97 and 1.98.
12. ☒ An assignment document for recording. A separate cover sheet in compliance with 37 CFR 3.28 and 3.31 is included.
13. ☐ A FIRST preliminary amendment.
☐ A SECOND or SUBSEQUENT preliminary amendment.
14. ☐ A substitute specification.
15. ☐ A change of power of attorney and/or address letter
16. ☒ Other items or information.

Associate Power of Attorney
International search report prepared by JPO
Forms PCT/IB/304 and PCT/IB/308
Front page of published International application



20277

PATENT TRADEMARK OFFICE

U.S. APPLIC. NO. (if known, see 37 CFR 1.50) <div style="font-size: 1.5em; font-weight: bold;">09/830939</div>		INTERNATIONAL APPLICATION NO PCT/JP99/06039		ATTORNEY'S DOCKET NUMBER 50212-207	
---	--	--	--	---------------------------------------	--

				CALCULATIONS	PTO USE ONLY
17. <input checked="" type="checkbox"/> The following fees are submitted: <div style="display: flex; justify-content: space-between;"> <div> Basic National Fee (37 CFR 1.492(a)(1)-(5)): Search Report has been prepared by the EPO or JPO International preliminary examination fee paid to USPTO (37 CFR 1.482) No international preliminary examination fee paid to USPTO (37 CFR 1.482) but international search fee paid to USPTO (37 CFR 1.445(a)(2)) Neither international preliminary examination fee (37 CFR 1.482) nor international search fee (37 CFR 1.445(a)(2)) paid to USPTO International preliminary examination fee paid to USPTO (37 CFR 1.482) and all claims satisfied provisions of PCT Article 33(2)-(4) </div> <div style="text-align: right;"> \$860.00 \$690.00 \$710.00 \$1,000.00 \$100.00 </div> </div> <div style="text-align: right; margin-top: 10px;"> ENTER APPROPRIATE BASIC FEE AMOUNT = </div>				<div style="border: 1px solid black; padding: 2px;">\$ 860.00</div>	
Surcharge of \$130.00 for furnishing the oath or declaration later than <input type="checkbox"/> 20 <input type="checkbox"/> 30 months from the earliest claimed priority date (37 CFR 1.492(e)).				<div style="border: 1px solid black; padding: 2px;">\$</div>	
Claims	Number Filed	Number Extra	Rate		
Total Claims	15 -20 =	0	x \$18.00	\$	
Independent Claims	2 -3 =	0	x \$80.00	\$	
Multiple dependent claim(s) (if applicable)			+ \$270.00	\$	
TOTAL OF ABOVE CALCULATIONS =				\$ 860.00	
Reduction by 1/2 for filing by small entity, if applicable. Verified Small Entity Statement must also be filed (Note 37 CFR 1.9, 1.27, 1.28)				\$	
SUBTOTAL =				\$ 860.00	
Processing fee of \$130.00 for furnishing the English translation later than the <input type="checkbox"/> 20 <input type="checkbox"/> 30 months from the earliest claimed priority date (37 CFR 1.492(f)).				\$	
TOTAL NATIONAL FEE =				\$ 860.00	
Fee for recording the enclosed assignment (37 CFR 1.21(h)). The assignment must be accompanied by an appropriate cover sheet (37 CFR 3.28, 3.31). \$40.00 per property				\$ 40.00	
TOTAL FEES ENCLOSED =				\$ 900.00	
				Amount to be: refunded	\$
				charged	\$

a. ☐ A check in the amount of \$ _____ to cover the above fees is enclosed.

b. ☒ Please charge my Deposit Account No 500417 in the amount of \$ 900.00 to cover the above fees. A duplicate copy of this sheet is enclosed.

c. ☒ The Commissioner is hereby authorized to charge any additional fees which may be required, or credit any overpayment to Deposit Account No 500417. A duplicate copy of this sheet is enclosed.

NOTE: Where an appropriate time limit under 37 CFR 1.494 or 1.495 has not been met, a petition to revive (37 CFR 1.137(a) or (b)) must be filed and granted to restore the application to pending status.

SEND ALL CORRESPONDENCE TO.

McDERMOTT, WILL & EMERY
 600 13th Street, N W
 Washington, DC 20005-3096
 (202) 756-8000
 Facsimile (202) 756-8087

SIGNATURE

Arthur J. Steiner

NAME

26,106

REGISTRATION NUMBER

May 3, 2001

DATE

09/830939

PATENT

Docket No.: 50212-207

JC08 Rec'd PCT/PTO

03 MAY 2001

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application of

Toshiki TARU, et al.

Serial No.:

Group Art Unit:

Filed: May 3, 2001

Examiner:

For: OPTICAL FIBER DRAWING METHOD AND OPTICAL FIBER DRAWING
FURNACE

PRELIMINARY AMENDMENT

Commissioner for Patents
Washington, DC 20231

Sir:

Prior to examination of the above-referenced application, please amend the application as follows:

IN THE SPECIFICATION AND CLAIMS:

Please substitute the attached pages of specification and claims as amended under Article 34 for the corresponding pages of specification and claims as filed. A marked up copy of the claims, indicating the changes, is attached.

REMARKS

Entry of this preliminary amendment is respectfully requested.

Respectfully submitted,

MCDERMOTT, WILL & EMERY


Arthur J. Steiner

Registration No. 26,106

600 13th Street, N.W.
Washington, DC 20005-3096
(202) 756-8000 AJS:klm
Date: May 3, 2001
Facsimile: (202) 756-8087

CLAIMS

1. (Amended) An optical fiber drawing method of optical fiber comprising steps of setting an optical fiber preform in a furnace core tube and a preform container connected to an upper portion of the furnace core tube and drawing an optical fiber from one end of said preform by heating and softening,

wherein an upper portion of said preform container is provided with an auxiliary heater and cooling means for cooling said upper portion of said preform container, and said drawing step includes adjusting a cooling quantity [of heat dissipation from said preform container] by said cooling means.

2. (Amended) An optical fiber drawing method according to Claim 1, wherein the adjustment of the cooling quantity [of heat dissipation from said preform container] by said cooling means is carried out based on the temperature measured at least at one position inside said preform container.

3. (Amended) An optical fiber drawing method according to Claim 1, wherein said auxiliary heater is disposed movable relative to an outer wall of said preform container and said adjustment of the cooling quantity [of heat dissipation] by said cooling means includes adjustment of a distance between the outer wall of said preform container and said auxiliary

heater.

4. (Amended) An optical fiber drawing method according to Claim 1, wherein said auxiliary heater is placed on an outer wall of said preform container, a heat insulator is disposed movable around the auxiliary heater, and said adjustment of the cooling quantity [of heat dissipation] by said cooling means includes adjustment of a distance between the outer wall of said preform container and said heat insulator.

5. (Amended) An optical fiber drawing method according to Claim 1, wherein said adjustment of the cooling quantity [of heat dissipation] by said cooling means includes adjustment of a quantity of a cooling fluid supplied to around an outer wall of said preform container.

6. An optical fiber drawing method according to Claim 5, wherein said cooling fluid is air or water.

7. (Amended) An optical fiber drawing furnace comprising a furnace core tube through which a fiber preform penetrates vertically, a heater disposed around said furnace core tube, and a preform container connected to an upper portion of said furnace core tube so as to be integral with said furnace core tube to form a semi-closed space opening in part at a lower end, for housing said fiber preform inside,

said fiber drawing furnace further comprising:

an auxiliary heater disposed at an upper portion of said preform container; and

[dissipation adjusting] cooling means for [adjusting a quantity of heat dissipation from] cooling the upper portion of said preform container.

8. (Amended) An optical fiber drawing furnace according to Claim 7, further comprising at least one temperature sensor for measuring an internal temperature in the upper portion of said preform container, wherein said [dissipation adjusting] cooling means includes a control unit for adjusting the cooling quantity [of heat dissipation] , based on the temperature measured by said temperature sensor.

9. (Amended) An optical fiber drawing furnace according to Claim 7, [further comprising] wherein said cooling means is air-providing means for supplying cooling air into clearance between said auxiliary heater and an outer wall of said preform container.

10. (Amended) An optical fiber drawing furnace according to Claim 7, wherein said cooling mean comprises [further comprising] heater moving means for moving said auxiliary heater to change a distance relative to said preform container.

11. An optical fiber drawing furnace according

to Claim 10, further comprising air-providing means for supplying cooling air into clearance between said preform container and said auxiliary heater, created by movement of said auxiliary heater.

5 12. (Amended) An optical fiber drawing furnace according to Claim 7, wherein said auxiliary heater comprises a heating element and a heat insulator formed around the heating element, [the fiber drawing furnace further comprising] said cooling means is insulator moving means for moving said heat insulator to change a distance relative to said preform container.

10 13. An optical fiber drawing furnace according to Claim 12, further comprising air-providing means for supplying cooling air into clearance between said heat insulator and said auxiliary heater, created by movement of said heat insulator.

15 14. (Amended) An optical fiber drawing furnace according to Claim 7, wherein said cooling means further [comprising] comprises a cooling fluid circulation path formed around said preform container and letting a cooling fluid flow inside, and supply means for supplying said cooling fluid into said circulation path.

20 15. An optical fiber drawing furnace according to Claim 14, wherein said cooling fluid is air or water.

9/PRTS

09/830939
JC08 Rec'd PCT/PTO 03 MAY 2001

VERIFICATION

The undersigned, of the below address, hereby certifies that he/she well knows both the English and Japanese languages, and that the attached is an accurate English translation of the PCT application filed on October 29, 1999 under

No. PCT/JP99/06039.

The undersigned declares further that all statements made herein of his/her own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issuing thereon.

Signed this 5th day of April, 2001.

Signature:


Name: Shiro TERASAKI

Address: c/o Soei Patent and Law Firm

Okura-Honkan, 6-12, Ginza 2-chome, Chuo-ku,

Tokyo 104-0061 Japan

09830939-050301

PTO/PCT Rec'd 03 MAY 2001

DESCRIPTION**OPTICAL FIBER DRAWING METHOD AND OPTICAL FIBER DRAWING FURNACE****5 Technical Field**

The present invention relates to a fiber drawing method of optical fiber capable of suppressing diameter fluctuations and to optical fiber drawing furnaces used in this method.

10 Background Art

Optical fibers are normally fabricated by softening with heat and drawing from an optical fiber preform shaped like a rod in the optical fiber drawing furnace. In order to reduce the production cost of optical fibers, it is effective to increase the length of the preform and thereby decrease the number of replacement works thereof. At the present time it is possible to make an optical fiber of the total length several hundred kilometers by single optical fiber drawing.

The drawing furnaces have also been improved in order to implement stable drawing of such an elongated fiber preform. The drawing furnace disclosed in Japanese Patent Application Laid-Open No. H09-2832 (which will be called hereinafter a prior art) is an example of such drawing furnaces for drawing of the

elongated fiber preform. This drawing furnace is constructed in such structure that a preform container cylinder is coupled to an upper portion of a furnace core tube provided with a heater surrounding it. Then the fiber preform is set in the preform container and the lower end thereof is guided into the furnace core tube. On the other hand, an inert gas such as helium or nitrogen is supplied from the upper end of the preform container. This keeps the furnace core tube and a semi-closed space above it (which will be referred to hereinafter simply as a semi-closed space) in a non-oxidizing atmosphere and the fiber preform is heated to soften from the lower end by the heater, followed by drawing.

During the drawing operation of optical fiber, the fiber preform becomes shorter and shorter with progress of fiber drawing. In the case of the drawing furnace with the preform container coupled, which is disclosed in this prior art, as the fiber preform becomes smaller with progress of fiber drawing, the space gradually becomes wider between the preform container and the fiber preform. It makes the inert gas in this space easier to flow and also increases a temperature difference between the inert gas in this space and the inert gas present between the furnace core tube and the fiber preform under drawing, so as to

cause convection of the inert gas in the semi-closed space.

Occurrence of such convection leads to instable flow of the atmosphere near the lower end of the fiber preform in the softened state with heat, i.e., near the outside of the opening end of the semi-closed space. It can affect the optical fiber under drawing so as to make the diameter fluctuations of optical fiber considerably large, thus making it difficult to obtain products with desired quality.

As countermeasures against it, the prior art discloses the technology of disposing an annular auxiliary heater around the upper end of the preform container and heating and retaining the inside of the upper end of the preform container at several hundred degrees. It is described that this technology can prevent occurrence of the convection in the semi-closed space and thus permit the optical fiber to be drawn in steady diameter.

Disclosure of the Invention

With the drawing furnace as above described, further increase in the length of the fiber preform will result in also extending the preform container housing it. It also increases the volume of the semi-closed space. It is obvious that the heating region by the auxiliary heater also has to be elongated in order

to prevent the unwanted convection in the semi-closed space.

5 The fiber preform of this kind is supported so as to be suspended from a support rod having the diameter smaller than the outside diameter of the preform in the preform container. The preform has a shoulder gradually decreasing its diameter toward the end, near a joint with the support rod. When the fiber preform is heated for drawing, this shoulder radiates a large quantity of heat, which also heats up the preform container facing it. With the elongation of the fiber preform accompanied by the expansion of the heating region inside the preform container, there is a possibility of overheating the internal wall of the preform container and eventually melting it. The shoulder of the fiber preform can also soften by the overheat, whereby the fiber preform undergoes axial extension in the shoulder part because of the weight of the fiber preform itself, so as to raise a possibility of failure in normal drawing of optical fiber.

20 In view of the above problem, an object of the present invention is to provide an optical fiber drawing method and an optical fiber drawing furnace capable of surely producing the optical fiber in steady diameter even in cases using the elongated fiber preform.

In order to accomplish the above object, an optical fiber drawing method according to the present invention is a drawing method of optical fiber comprising steps of setting an optical fiber preform in a furnace core tube and a preform container connected to an upper portion of the furnace core tube and drawing an optical fiber from one end of the preform by softening with heat, wherein an upper portion of the preform container is provided with an auxiliary heater and cooling means for cooling the upper portion of the preform container, and the drawing step includes adjusting a cooling quantity by said cooling means.

Namely, a drawing furnace used in this drawing method is a fiber drawing furnace comprising a furnace core tube through which an optical fiber preform penetrates vertically, a heater disposed around this furnace core tube, and a preform container connected to an upper portion of the furnace core tube so as to be integral with the furnace core tube to form a semi-closed space opening in part at a lower end, for housing the fiber preform inside, the fiber drawing furnace further comprises an auxiliary heater disposed at an upper portion of the preform container and cooling means for cooling the upper portion of the preform container.

The present invention permits the temperature difference to be reduced in the space of clearance to the fiber preform in the semi-closed space formed by the furnace core tube and the preform container, so as to suppress

occurrence of convection described above, even in the case of the elongated fiber preform. Further, cooling the upper portion of the preform container prevents the overheat of the internal wall of the preform container and, in turn, prevents the overheat of the shoulder of the fiber preform, which permits the optical fiber to be surely drawn in steady diameter and which prevents breakage of the drawing furnace.

Here the drawing furnace is preferably one further comprising at least one temperature sensor for measuring an internal temperature of the upper portion of the preform container and adjusting the cooling quantity based on the temperature measured by the temperature sensor.

It is preferable to employ either of the following techniques for the cooling quantity from the upper portion of the preform container.

For example, the cooling quantity may be adjusted by supplying cooling air into clearance between the auxiliary heater and the outer wall of the preform container. Another technique is to adjust the cooling quantity by heater moving means for moving the auxiliary heater to change the distance to the preform container. In this case, it is also optional to supply the cooling air into the clearance between the preform container and the auxiliary heater, which is created by movement of the auxiliary heater.

In another technique, the auxiliary heater has a heating element and a heat insulator formed around it and

difference to be reduced in the space of clearance to the fiber preform in the semi-closed space formed by the furnace core tube and the preform container, so as to suppress occurrence of convection described above, even in the case of the elongated fiber preform. Further, the adjustment of the quantity of heat dissipation from the upper portion of the preform container prevents the overheat of the internal wall of the preform container and, in turn, prevents the overheat of the shoulder of the fiber preform, which permits the optical fiber to be surely drawn in steady diameter and which prevents breakage of the drawing furnace.

Here the drawing furnace is preferably one further comprising at least one temperature sensor for measuring an internal temperature of the upper portion of the preform container and adjusting the quantity of heat dissipation, based on the temperature measured by the temperature sensor.

It is preferable to employ either of the following techniques for the adjustment of the quantity of heat dissipation from the upper portion of the preform container.

For example, the quantity of heat radiation may be adjusted by supplying cooling air into clearance between the auxiliary heater and the outer wall of the

the cooling quantity is adjusted by moving the heat insulator to change the distance to the preform container. In this case, it is also optional to supply the cooling air into the clearance between the heat insulator and the auxiliary heater, which is created by movement of the heat insulator.

In another technique, the furnace may further comprise a cooling fluid circulation path which is formed around the preform container and in which a cooling fluid flows, and supply means for supplying the cooling fluid into the circulation path. This cooling fluid is preferably air or water.

Brief Description of the Drawings

Fig. 1 is a cross-sectional view to show the structure of the first embodiment of the optical fiber drawing furnace according to the present invention, Fig. 2 is an enlarged view to show the major part thereof,

and Fig. 3 is a cross-sectional view along a line III-III in Fig. 2. Fig. 4 is a drawing to show an example of a heater moving device.

Fig. 5 to Fig. 8 are cross-sectional views each showing the upper preform container part and the heater moving device in other embodiments of the optical fiber drawing furnace according to the present invention.

Fig. 9 is a cutaway view to show the structure of the major part of the fifth embodiment of the optical fiber drawing furnace according to the present invention, and Fig. 10 is a cross-sectional view along a line X-X of Fig. 9.

Fig. 11 is a view to show the structure of the major part of the sixth embodiment of the optical fiber drawing furnace according to the present invention.

Best Mode for Carrying out the Invention

The preferred embodiments of the present invention will be described hereinafter in detail with reference to the accompanying drawings. To facilitate the comprehension of the explanation, the same reference numerals denote the same parts, where possible, throughout the drawings, and a repeated explanation will be omitted.

Fig. 1 is a cross-sectional view to show the structure of the first embodiment of the optical fiber drawing furnace according to the present invention, Fig.

2 an enlarged view to show the major part thereof, and
Fig. 3 a cross-sectional view along a line III-III in
Fig. 2.

This optical fiber drawing furnace is provided
with a furnace body 11 made of stainless steel and
lined inside with a heat insulator. A cylindrical
furnace core tube 12 is disposed in the central part of
this furnace body 11 and an annular carbon heater 15 is
placed around it, i.e., between the furnace core tube
12 and the furnace body 11. The furnace core tube 12
and the carbon heater 15 are concentrically arranged.
The cylindrical space inside the furnace core tube 12
will be called hereinafter a core chamber 10.

During drawing, a fiber preform 13, an upper end
of which is coupled through a joint 17 to a lower end
of support rod 16 held by a chuck not shown, is fed
from the lower end side thereof along the center axis
of the core chamber 10 and an optical fiber 14 is
formed by heating and drawing. A seal sheet 19, having
a through hole 18 for letting the optical fiber 14 pass
in the center, is attached to the lower end of the
furnace body 11. When the fiber preform 13 is large,
it is preferable to provide a cylindrical furnace core
tube extension instead of the seal sheet 19.

A cooling jacket connected to a refrigerant
circulator not shown is incorporated in this furnace

body 11 and the inside of the core chamber 10 is maintained at a predetermined temperature by controlling supply rates and temperatures of a refrigerant from the refrigerant circulator into the cooling jacket in combination with heating of the carbon heater 15 by a control unit 29 described hereinafter.

Preform container cylinders 21, 22 made of a heat resistant alloy such as inconel or the like are connected to the upper end of the furnace body 11. The internal wall of the furnace core tube 12 is extended to be integrated with the internal walls of the preform containers 21, 22, thereby forming an upper chamber 20. As a result, the furnace core tube 12 and the preform containers 21, 22 form a semi-closed space (the upper chamber 20 and core chamber 10) having the aperture 18 at the lower end. Here the preform container part does not always have to be constructed in the structure of Fig. 1, but may also be constructed by connecting three or more cylindrical members in series, or may be integrally formed.

A shuttering 24, which has an opening 23 of a small diameter for letting the support rod 16 pass so as to be slidable in the center, is attached to the upper end of the preform container 21 to maintain airtightness inside the upper chamber 20. Further, a

gas inlet port not shown is provided at the upper end of the preform container 21. A supply of inert gas such as helium or nitrogen is connected through a gas supply tube to the gas inlet port. The inert gas is supplied from this inert gas supply through the gas supply tube and gas inlet port to the upper end of the upper chamber 20 to maintain the inside of the chambers 10 and 20 as the semi-closed space in the inert gas atmosphere.

Around this upper preform container 21, there are auxiliary heaters 25 of an arcuate shape arranged in a vertical two-stage configuration. Each of these auxiliary heaters 25 has an iron-chromium-aluminum-based heating wire 27 and a heat insulator 28 of ceramic fiber surrounding this heating wire to hold it. Two halves of each heater are arranged in symmetry with the preform container 21 in between and clearance 31 is formed between them, as shown in Fig. 3. A plurality of temperature sensors 30 for measuring the temperature of the wall of the preform container 21 are placed in this part of clearance 31.

Then each of the heating wires 27 is connected to the control unit 29 for controlling power supply states to them. Each of the temperature sensors 30 described above is connected to this control unit 29 to send each control information thereto.

The auxiliary heaters 25 are connected to a heater moving device 33, and by actuating this heater moving device 33, the distance between the auxiliary heaters 25 and the preform container 21 can be adjusted between a heating position shown by chain double-dashed lines and a dissipating position shown by solid lines in Fig. 3.

Fig. 4 is a view to show an example of this heater moving device. The auxiliary heater 25 is mounted so as to be movable on rails 332 attached to the preform container 21. Then motors 330 are driven to move the auxiliary heater 25 toward or away from the preform container 21 through shafts 331 attached to the auxiliary heater 25. The auxiliary heater 25 can be translationally moved by using linear motors as the motors 330 or by placing rack-and-pinion gears between the motors 330 and the shafts 331.

Next described in detail is the operation of the present embodiment, i.e., the drawing method of optical fiber according to the present invention.

The upper end of the fiber preform 13 is coupled through the joint 17 to the lower end of the support rod 16. Then this support rod 16 is held by the chuck not shown, whereby the fiber preform 13 is set in the upper chamber 20, i.e., inside the preform containers 21, 22. Then the shuttering 24 is attached so as to

allow the support rod 16 to slide in the aperture 23.

In this state the inert gas is supplied from the inert gas supply source not shown through the gas supply tube and gas inlet port into the upper chamber 20 to fill the inside of the thus-created semi-closed space with the inert gas atmosphere.

After that, the fiber preform 13 is fed from the lower end thereof into the core chamber 10. The fiber preform 13 is heated in the core chamber 10 by the carbon heater 15 to melt and soften and then fiber drawing is carried out to make the optical fiber 14.

In the initial stage of drawing (see Fig. 2) in which the fiber preform 13 is sufficiently long and in which the shoulder 26 with diameters gradually decreasing at the upper end is located inside the upper preform container 21, the volume of space is small above this shoulder 26 in the upper chamber 20, so that great thermal convection is unlikely to occur.

However, if the drawing should be carried out simply, the following problem would arise. The heat radiation from the carbon heater 15 is incident on the lower end of the fiber preform 13, passes through the cylindrical body thereof, and radiates from the shoulder 26. This causes increase in the temperature of the internal wall of the preform container 21 and could melt the preform container 21 in the worst case.

Even if the melting of the preform container 21 is not encountered, the fiber preform 13 could soften in the shoulder 26 because of the increase in the temperature of the shoulder 26 and be extended by the dead weight thereof. It can result in great diameter fluctuations of the optical fiber 14 and the fiber preform 13 itself can break at the shoulder 26 to drop in the worst case.

This phenomenon can occur when the temperature in the upper part of the preform container 21 exceeds 800°C. In the present embodiment, therefore, the control unit 29 monitors the temperature of the preform container 21 by the temperature sensors 30. When the temperature measured exceeds a predetermined temperature, the control unit 29 actuates the heater moving device 33 to move the auxiliary heaters 25 away from the preform container 21 as shown by the solid lines in Fig. 3. This creates the clearance 32 of about 4 to 5 cm between the external wall of the preform container 21 and the auxiliary heaters 25 to promote dissipation of heat from the external wall of the preform container 21 to the outside air passing this clearance 32, thereby cooling the preform container 21 and preventing the overheat thereof.

A necessary condition is that the temperature of the preform container 21 is controlled not more than 800°C, as described above, but it is preferable to

control the temperature not more than 700°C in terms of assurance of lifetime for the drawing furnace and stability of fabrication of the optical fiber 14. In this case, preferably, the control unit 29 cuts off the power supply to the auxiliary heaters 25 to bring them into a non-heating state.

The fiber preform 13 descends in the upper chamber 20 with progress of drawing and the shoulder 26 also descends. This results in increase in the volume of the space above the shoulder 26 in the upper chamber 20. When the volume of the space in this portion increases considerably, the temperature of the gas decreases in the upper part in this space. Then thermal convection can occur from the heat source of the shoulder 26 in the space above the shoulder 26 of the fiber preform 13. This thermal convection becomes conspicuous when the temperature of the preform container 21 becomes less than 300°C.

In the present embodiment, as described previously, the control unit 29 monitors the temperature of the preform container 21 by the temperature sensors 30. When the measured temperature becomes lower than a predetermined temperature, the control unit 29 actuates the heater moving device 33 to move the auxiliary heaters 25 before they abut on the outer wall of the preform container 21 as shown by the

chain double-dashed lines in Fig. 3. Then the auxiliary heaters 25 are activated to heat the preform container 21 and thereby heat the atmosphere in the upper chamber 20, thereby preventing the aforementioned occurrence of thermal convection.

The temperature of the preform container 21 at this time needs to be adjusted to not less than 300°C and it is preferable to adjust the temperature to not less than 400°C.

By adjusting the quantity of heat dissipation from the outer wall of the preform container 21 in this way, the present embodiment can finely adjust the temperature of the preform container 21 and, in turn, the temperature of the atmosphere in the upper chamber 20 inside thereof and thus prevent the occurrence of thermal convection and the overheat of the preform container 21 and the shoulder 26 of the fiber preform 13. As a consequence, the drawing of the optical fiber 14 can be carried out on a stable basis.

Fig. 5 is a cross-sectional view of the upper preform container part in the second embodiment of the fiber drawing furnace according to the present invention. In the present embodiment the auxiliary heater 25a is constructed by attaching a heating wire coated with an electric insulator and a heat resistant alloy, to the outer wall of the preform container 21.

Only heat insulators 28a are arranged movable by an insulator moving device 33a. This insulator moving device 33a is a device similar to the heater moving device 33 in the first embodiment (see Fig. 3).

5 In the present embodiment, the clearance 32 between the heat insulators 28a and the auxiliary heater 25a is adjusted by moving the heat insulators 28a between the heating position shown by chain double-dashed lines and the dissipating position shown by solid lines, by the insulator moving device 33a. This implements adjustment of heat dissipation from the external wall of the auxiliary heater 25a, so as to be able to adjust the quantity of heat dissipation from the preform container 21, whereby the drawing of the optical fiber 14 can be performed on a stable basis.

10 In these embodiments, each of the auxiliary heaters 25 or the heat insulators 28a has the cross-sectional shape of semicircular arches formed by dividing a cylinder into two parts. However, the shape of the auxiliary heaters 25 or the heat insulators 28a is not limited to this, but they may be formed in the shape obtained by dividing a cylinder into three or more parts in the circumferential direction. Another applicable configuration is a C-shaped sectional structure obtained by cutting out part of a side face of a cylinder along the longitudinal direction thereof,

and the clearance 32 to the preform container 21 is expanded by elastic deformation of the cylinder while widening the width of this cut part.

Fig. 6 is a cross-sectional view of the upper preform container 21 in the fiber drawing furnace of the third embodiment having the auxiliary heater 25 of this type. Namely, the auxiliary heater 25 in the present embodiment has the approximately cylindrical shape of the C-shaped sectional structure. Then the width of the clearance 31 of the cut part is expanded by driving the heater moving device 33. This causes the elastic deformation of the auxiliary heater 25 and moves the heater from the heating position shown by chain double-dashed lines to the dissipating position shown by solid lines, thereby expanding the clearance 32 between the preform container 21 and the auxiliary heater 25. The quantity of heat dissipation from the preform container 21 is adjusted in the same manner as in the first and second embodiments by adjusting this clearance 32, whereby the drawing of the optical fiber 14 can be performed on a stable basis.

Fig. 7 is a diagram to show a specific example of the heater moving device 33 in this embodiment. A belt 333 is wrapped around the auxiliary heater 25 and the clearance 32 between the preform container 21 and the auxiliary heater 25 is adjusted by controlling the

distance of the cut part of this belt 333 by motors 330a and shafts 331a.

Fig. 8 is a cross-sectional view of the upper preform container part in the fourth embodiment of the fiber drawing furnace according to the present invention. In the present embodiment the auxiliary heater 25a is constructed by attaching a heating wire coated with an electric insulator and a heat resistant alloy, to the external wall of the preform container 21 in the same manner as in the second embodiment. Only a heat insulator 28a having the C-shaped cross section similar to that in the third embodiment is arranged movable by the insulator moving device 33a. This insulator moving device 33a is a device similar to that in the second embodiment.

In the present embodiment the clearance 32 between the insulator 28a and the auxiliary heater 25a is also adjusted by expanding the clearance 31 in the cut part of the insulator 28a by the insulator moving device 33a. This permits the quantity of heat dissipation from the preform container 21 to be adjusted by controlling the dissipation from the external wall of the auxiliary heater 25a, whereby the drawing of the optical fiber 14 can be performed on a stable basis.

These first to fourth embodiments all are

arranged to adjust the heat dissipation from the external wall of the preform container 21 by natural air cooling, but it is also possible to make use of forced cooling. Fig. 9 and Fig. 10 respectively
5 present a cutaway structural view and a cross-sectional view along a line X-X of the major part of the fifth embodiment of the fiber drawing furnace of the present invention making use of the forced cooling.

In the present embodiment the auxiliary heater 25
10 is of a cylindrical form, different from the auxiliary heaters 25 in the first and third embodiments. The clearance 32 of about 5 cm is formed between the heater and the preform container 21, also different from the auxiliary heaters 25a in the second and fourth
15 embodiments. Annular heat insulators 34 are placed in close fit with the preform container 21 at the upper and lower ends, respectively, of the auxiliary heater 25, so as to seal the clearance 32. Since the present embodiment employs the structure in which the heating
20 wire 27 of the auxiliary heater 25 is exposed to the clearance 32, it is preferable to use a nickel-chromium-based or iron-chromium-based heating body with excellent oxidation resistance.

The auxiliary heater 25 is equipped with an inlet
25 tube 35 penetrating the heater from the outside thereof into the internal clearance 32 and an exhaust tube 36

penetrating the heater from the internal clearance 32 to the outside thereof. Shutters 38, which can be controlled to be opened or closed simultaneously, are disposed at respective opening ends of the inlet tube 35 and the exhaust tube 36 outside the cylinder and their open/close positions are controlled by a shutter driving device 37 actuated by the control unit 29. An air-providing pump 50 is further connected through a supply tube 51 to the inlet tube 35 so as to be able to blow air into the clearance 32.

During the fiber drawing operation of the optical fiber by use of the present embodiment, the control unit 29 monitors the temperature of the preform container 21 by the temperature sensors 30 in the same manner as in the other embodiments. When the temperature of the preform container 21 is about to become not less than 700°C, the power supply is terminated to the auxiliary heater 25 (heating wire 27), the shutters 38 are opened, and the air-providing pump 50 is actuated to supply the cooling air of as large as 5 m³ per minutes through the supply tube 51 and inlet tube 35 into the clearance 32. The blowing air forcedly cools the preform container 21 from the outside, so that the temperature of the preform container 21 is maintained not more than the predetermined temperature. As a result, the hot air is

discharged through the exhaust tube 36 into the atmosphere.

On the other hand, when the temperature of the preform container 21 is about to become not more than 400°C, the air-providing pump 50 is stopped and the shutters 38 are closed, so as to keep the clearance 32 perfectly in a hermetic state. Then the power is supplied to the auxiliary heater 25 (heating wire 27) to heat the preform container 21 from the external wall.

In the present embodiment, as shown in Fig. 10, the cooling air is supplied from the tangential direction into the clearance 32 to make a turning flow in the clearance 32, thereby enhancing the heat dissipation effect from the outside wall of the preform container 21. Besides it, it is also possible to accomplish the same effect by partitioning the inside of the clearance 32 in spiral structure.

The cooling fluid for the forced cooling can also be either of liquids such as water, oil, and the like, as well as the air. Fig. 11 is a view to show the schematic structure of the major part of the sixth embodiment of the fiber drawing furnace of the present invention employing this liquid cooling method.

In the present embodiment a heat-transfer plate 39 made of stainless steel or the like is attached to the periphery of the auxiliary heater 25. A tube is

further wrapped around this heat-transfer plate 39 to form a cooling coil 40 and a heat insulator 41 is placed so as to surround it.

One end of the cooling coil 40 is connected through a flow control valve 42 and a pump 43 to a water tank 44, and the other end is connected through a condenser 45 to this water tank 44, thus forming a circulation path. Cooling water W is reserved in this water tank 44 and an air vent 46 is provided at the upper end of the water tank 44. An air pump 48 is connected through a switching valve 47 to between the cooling coil 40 and the flow control valve 42. The control unit 29 controls opening/closing of these flow control valve 42 and switching valve 47 and the operation of the pumps 43, 48.

During the fiber drawing operation of the optical fiber in the present embodiment, the control unit 29 monitors the temperature measured by the temperature sensors 30. When the temperature of the preform container 21 increases to raise the necessity of heat dissipation, the control unit 29 closes the switching valve 47, activates the pump 43, and controls the flow regulator valve 42 to let the cooling water W flow at a predetermined flow rate in the cooling coil 40, thereby forcedly cooling the preform container 21 and promoting heat dissipation from the upper chamber 20.

The cooling water W heated to evaporate during the cooling of the preform container 21 is condensed by the condenser 45 and then returned to the water tank 44. Even if the returned cooling water W at the high
5 temperature increases the temperature of the water inside the water tank 44, vapor will be discharged through the air vent 46 whereby the pressure inside the water tank 44 is maintained at the atmospheric pressure.

When the temperature of the preform container 21 becomes too low on the other hand, the control unit 29 stops the operation of the pump 42, closes the flow control valve 42, opens the switching valve 47, and activates the air pump 47 to force air into the cooling coil 40, thereby discharging the cooling water W
10 remaining in the cooling coil 40 toward the condenser 45. After that, the control unit stops the air pump 47 and closes the switching valve 47 to keep the inside of the cooling coil 40 in a hermetic state. Then the control unit energizes the heating wire 27 to heat the
15 preform container 21 from the outside, so as to maintain the temperature not less than the predetermined temperature.

This embodiment described the example in which the cooling coil 40 was disposed outside the auxiliary
20 heater 25, but the cooling coil 40 may be disposed
25 inside the heat insulator 28 of the auxiliary heater 25.

5 The inventors actually conducted the fiber
drawing from the long fiber preform 13 (having the
length of 1.8 m and the diameter of 9 cm) with
adjusting the temperature of the preform container 21
in the range of 400 to 700°C, using these fiber drawing
furnaces. It was verified from the result of the fiber
drawing that the optical fiber 14 was able to be
produced with less diameter fluctuations, i.e., in the
diameter of $125\ \mu\text{m} \pm 0.1\ \mu\text{m}$ throughout the entire
length (900 km).

Industrial Applicability

15 The fiber drawing furnaces and fiber drawing
method according to the present invention are suitably
applicable to stable fabrication of the optical fiber
with less diameter fluctuations, particularly, by use
of the long fiber preform.

CLAIMS

1. (Amended) An optical fiber drawing method of optical fiber comprising steps of setting an optical fiber preform in a furnace core tube and a preform container connected to an upper portion of the furnace core tube and drawing an optical fiber from one end of said preform by heating and softening,

wherein an upper portion of said preform container is provided with an auxiliary heater and cooling means for cooling said upper portion of said preform container, and said drawing step includes adjusting a cooling quantity by said cooling means.

2. (Amended) An optical fiber drawing method according to Claim 1, wherein the adjustment of the cooling quantity by said cooling means is carried out based on the temperature measured at least at one position inside said preform container.

3. (Amended) An optical fiber drawing method according to Claim 1, wherein said auxiliary heater is disposed movable relative to an outer wall of said preform container and said adjustment of the cooling quantity by said cooling means includes adjustment of a distance between the outer wall of said preform container and said auxiliary heater.

4. (Amended) An optical fiber drawing method according to Claim 1, wherein said auxiliary heater is placed on an outer wall of said preform container, a heat insulator is disposed movable around the auxiliary heater, and said adjustment of the cooling quantity by said cooling means includes adjustment of a distance between the outer wall of said preform container and said heat insulator.

5. (Amended) An optical fiber drawing method according to Claim 1, wherein said adjustment of the cooling quantity by said cooling means includes adjustment of a quantity of a cooling fluid supplied to around an outer wall of said preform container.

6. An optical fiber drawing method according to Claim 5, wherein said cooling fluid is air or water.

7. (Amended) An optical fiber drawing furnace comprising a furnace core tube through which a fiber preform penetrates vertically, a heater disposed around said furnace core tube, and a preform container connected to an upper portion of said furnace core tube so as to be integral with said furnace core tube to form a semi-closed space opening in part at a lower end, for housing said fiber preform inside,

said fiber drawing furnace further comprising:

an auxiliary heater disposed at an upper portion of said preform container; and

cooling means for cooling the upper portion of said preform container.

5 8. (Amended) An optical fiber drawing furnace according to Claim 7, further comprising at least one temperature sensor for measuring an internal temperature in the upper portion of said preform container, wherein said cooling means includes a control unit for adjusting the cooling quantity, based on the temperature measured by said temperature sensor.

10 9. (Amended) An optical fiber drawing furnace according to Claim 7, wherein said cooling means is air-providing means for supplying cooling air into clearance between said auxiliary heater and an outer wall of said preform container.

15 10. (Amended) An optical fiber drawing furnace according to Claim 7, wherein said cooling mean comprises heater moving means for moving said auxiliary heater to change a distance relative to said preform container.

20 11. An optical fiber drawing furnace according to Claim 10, further comprising air-providing means for supplying cooling air into clearance between said

preform container and said auxiliary heater, created by movement of said auxiliary heater.

12. (Amended) An optical fiber drawing furnace according to Claim 7, wherein said auxiliary heater comprises a heating element and a heat insulator formed around the heating element, said cooling means is insulator moving means for moving said heat insulator to change a distance relative to said preform container.

13. An optical fiber drawing furnace according to Claim 12, further comprising air-providing means for supplying cooling air into clearance between said heat insulator and said auxiliary heater, created by movement of said heat insulator.

14. (Amended) An optical fiber drawing furnace according to Claim 7, wherein said cooling means further comprises a cooling fluid circulation path formed around said preform container and letting a cooling fluid flow inside, and supply means for supplying said cooling fluid into said circulation path.

15. An optical fiber drawing furnace according to Claim 14, wherein said cooling fluid is air or water.

ABSTRACT

A fiber drawing method according to the present invention is a drawing method of optical fiber for drawing an optical fiber 14 from one end of a fiber preform 13 by softening with heat, wherein the fiber preform 13 is set in a semi-closed space 10, 20 opening in part at a lower end in a fiber drawing furnace, the fiber preform 13 is heated by a heater 15 disposed on the lower end side of this semi-closed space 10, 20, and fiber drawing is carried out with adjusting a quantity of heat dissipation from the upper portion 20 of this semi-closed space.


Fig.1


Fig.2

Fig.3




Fig.4





Fig.5




Fig.6**Fig.7**

Fig.8

SECRET






Fig.10



Combined Declaration and Power of Attorney

As a below named inventor, I hereby declare that:

This declaration is of the following type:

☒ original ☐ supplemental

☒ national stage of PCT

☐ divisional ☐ continuation ☐ continuation-in-part

My residence, post office address and citizenship are as stated next to my name,

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

OPTICAL FIBER DRAWING METHOD AND OPTICAL FIBER DRAWING FURNACE

the specification of which

☐ is attached hereto.

☐ was filed on _____
as United States Application Serial Number _____ and,
was amended on _____ (if applicable).

☒ was filed on October 29, 1999
as PCT International Application Number PCT/JP99/06039 and,
was amended under PCT Article 19 on _____ (if applicable).

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56.

I hereby claim foreign priority under Title 35, United States Code, Section 119(a)-(d) or 365(b) of any foreign application(s) for patent or inventor's certificate, or 365(a) of any PCT International application which designated at least one country other than the United States, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate, or PCT International application having a filing date before that of the application on which priority is claimed.

PRIOR FOREIGN APPLICATIONS, BENEFIT CLAIMED UNDER 35 USC §119(a)

Application Number	Country	Date of Filing (Day/Month/Year)	Priority Claimed Under 35 USC 119
<u>P1998-324181</u>	<u>Japan</u>	<u>13 / November / 1998</u>	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> Yes <input type="checkbox"/> No

01/10/99-05-00
SE199-29

I hereby claim the benefit under Title 35, United States Code, Section 119(e) of any United States provisional application(s) listed below.

PRIOR U.S. PROVISIONAL APPLICATIONS, BENEFIT CLAIMED UNDER 35 USC §119(e)

_____ (Application No.)	_____ (Filing Date)	_____ (Application No.)	_____ (Filing Date)
_____ (Application No.)	_____ (Filing Date)	_____ (Application No.)	_____ (Filing Date)

I hereby claim the benefit of Title 35, United States Code Section 120 of any United States application(s), or 365(c) of any PCT International application designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of Title 35, United States Code Section 112, I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56 which became available between the filing date of the prior application and the national or PCT International filing date of this application:

PRIOR U.S. APPLICATIONS OR PCT INTERNATIONAL APPLICATIONS
DESIGNATING THE U.S., BENEFIT CLAIMED UNDER 35 USC §120

PCT/JP99/06039	October 29, 1999	Pending
_____ (Application No.)	_____ (Filing Date)	_____ (Status: Patented, Pending, Abandoned)
_____ (Application No.)	_____ (Filing Date)	_____ (Status: Patented, Pending, Abandoned)

POWER OF ATTORNEY: As a named inventor, I hereby appoint the registered practitioners of MCDERMOTT, WILL & EMERY included in the Customer Number provided below to prosecute this application and transact all business in the Patent and Trademark Office connected therewith.

Customer Number 20277

Send Correspondence to: Customer Number 20277

MCDERMOTT, WILL & EMERY

600 13TH STREET, N.W.
WASHINGTON, D.C., 20005-3096

Direct Telephone Calls to: 202-756-8000

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issuing thereon.

Full Name of sole or first inventor Toshiki TARU	
Inventor's signature <i>Toshiki Taru</i>	Date <i>March, 23, 2001</i>
Residence <u>Yokohama-shi</u> , Kanagawa, Japan <i>JPX</i>	
Citizenship Japan	
Post office address c/o Yokohama Works of Sumitomo Electric Industries, Ltd., 1, Taya-cho, Sakae-ku, Yokohama-shi, Kanagawa 244-8588 Japan	

Full Name second joint inventor, if any Ichiro TSUCHIYA	
Second inventor's signature <i>Ichiro Tsuchiya</i>	Date <i>Apr. 2, 2001</i>
Residence <u>Yokohama-shi</u> , Kanagawa, Japan <i>JPX</i>	
Citizenship Japan	
Post office address c/o Yokohama Works of Sumitomo Electric Industries, Ltd., 1, Taya-cho, Sakae-ku, Yokohama-shi, Kanagawa 244-8588 Japan	

Full Name third joint inventor, if any Katsuyuki TSUNEISHI	
Third inventor's signature <i>Katsuyuki Tsuneishi</i>	Date <i>April. 2. 2001</i>
Residence <u>Yokohama-shi</u> , Kanagawa, Japan <i>JPX</i>	
Citizenship Japan	
Post office address c/o Yokohama Works of Sumitomo Electric Industries, Ltd., 1, Taya-cho, Sakae-ku, Yokohama-shi, Kanagawa 244-8588 Japan	

Full Name fourth joint inventor, if any Katsuya NAGAYAMA	
Fourth inventor's signature <i>Katsuya Nagayama</i>	Date <i>March, 26, 2001</i>
Residence <u>Yokohama-shi</u> , Kanagawa, Japan <i>JPX</i>	
Citizenship Japan	
Post office address c/o Yokohama Works of Sumitomo Electric Industries, Ltd., 1, Taya-cho, Sakae-ku, Yokohama-shi, Kanagawa 244-8588 Japan	

5.00

Full Name fifth joint inventor, if any Kazuya KUWAHARA	
Fifth inventor's signature <i>Kazuya Kuwahara</i>	Date <i>April. 2. 2001</i>
Residence Yokohama-shi, Kanagawa, Japan <i>JA</i>	
Citizenship Japan	
Post office address c/o Yokohama Works of Sumitomo Electric Industries, Ltd., 1, Taya-cho, Sakae-ku, Yokohama-shi, Kanagawa 244-8588 Japan	

099/05-US-05
SE199-29

PTO/PCT Rec'd 33 MAY 2001

Docket No.: 50212-207

PATENT

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application of :
Toshiki TARU, et al. :
Serial No.: : Group Art Unit:
Filed: May 3, 2001 : Examiner:
For: OPTICAL FIBER DRAWING METHOD AND OPTICAL FIBER DRAWING
FURNACE

ASSOCIATE POWER OF ATTORNEY

Honorable Commissioner for Patents and Trademarks
Washington, D. C. 20231

Sir:

The undersigned Principal Attorney of record hereby appoints the following Attorneys as his Associates with regard to the above-identified application: Stephen A. Becker, Reg. No. 26,527; John G. Bisbikis, Reg. No. 37,095; Christopher D. Bright, Reg. No. 46,578; Daniel Bucca, Reg. No. 42,368; Kenneth L. Cage, Reg. No. 26,151; Jennifer Chen, Reg. No. 42,404; Bernard P. Codd, Reg. No. 46,429; Lawrence T. Cullen, Reg. No. 44,489; Paul Devinsky, Reg. No. 28,553; Margaret M. Duncan, Reg. No. 30,879; Shamita De. Etienne-Cummings, Reg. No. 46,072; Ramyar M. Farid, Reg. No. 46,692; Brian E. Ferguson, Reg. No. 36,801; Michael E. Fogarty, Reg. No. 36,139; John R. Fuisz, Reg. No. 37,327; Willem F. Gadiano, Reg. No. 37,136; Keith E. George, Reg. No. 34,111; Matthew V. Grumbling, Reg. No. 44,427; John A. Hankins, Reg. No. 32,029; Joseph Hyosuk Kim, Reg. No. 41,425; Eric J. Kraus, Reg. No. 36,190; Catherine Krupka, Reg. No. 46,227; Jack Q. Lever, Reg. No. 28,149; Raphael V. Lupo, Reg. No. 28,363; Michael A. Messina, Reg. No. 33,424; Dawn L. Palmer, Reg. No. 41,238; Joseph H. Paquin, Jr., Reg. No. 31,647; Scott D. Paul, Reg. No. 42,984; William D. Pegg, Reg. No. 42,988; Robert L. Price, Reg. No. 22,685; Gene Z. Robinson, Reg. No. 33,351; Joy Ann G. Serauskas, Reg. No. 27,952; Daniel H. Sherr, Reg. No. 46,425; David A. Spenard, Reg. No. 37,449; Arthur J. Steiner, Reg. No. 26,106; David L. Stewart, Reg. No. 37,578; Wesley Strickland, Reg. No. 44,363; Michael D. Switzer, Reg. No. 39,552; Daniel S. Trainor, Reg. No. 43,959; Cameron K. Weiffenbach, Reg. No. 44,488; Aaron Weisstuch, Reg. No. 41,557; Edward J. Wise, Reg.

Serial No.:

No. 34,523; Jeffrey A. Woller, Reg. No. 48,041; Alexander V. Yampolsky, Reg. No. 36,324; and Robert W. Zelnick, Reg. No. 36,976 all of

McDERMOTT, WILL & EMERY
600 13th Street, N.W.
Washington, DC 20005-3096

Please continue to address all communications to the undersigned.

May 3, 2001

By Arthur J. Steiner
Arthur J. Steiner
Registration No. 26,106
Attorney for Applicant

FD-050" 5E60E350